

# Instruction Manual

## Drum Tongs



**DM500**

**Note:** The Owner/Operator must read carefully and understand all the information presented here before operation.

THANK YOU FOR USING THIS DRUM TONGS. FOR YOUR SAFETY AND CORRECT OPERATION, PLEASE CAREFULLY READ THIS INSTRUCTION BEFORE USING IT.

**NOTE:** All of the information reported herein is based on data available at the moment of printing. The factory reserves the right to modify its own products at any moment without notice and incurring in any sanction. So it is suggested to always verify possible updates.

## **WARNING**

- Read and understand the entire owner's manual before using the drum tongs.
- These drum tongs are designed for lifting open or closed 55 gallon steel drums in horizontal position.
- Do not load the drum tongs beyond their rated capacity of 1,100 lbs.
- Inspect the drum tongs before each use. If there is damage or distortion to any part, the drum tongs must be removed from service until they are repaired or replaced.
- Make sure the drum is secured by the tongs before raising.
- Do not allow anyone to stand beneath a raised drum.
- Never leave a drum unattended in the raised position.
- Do not use these drum tongs for other than their intended use.
- Failure to comply with these warnings may result in personal injury and/or property damage

## **OPERATION OF MANUAL DRUM TONGS**

1. Place the drum tongs upon the hook of your hoist, chain block, crane, etc.
2. Lower the tongs over the drum, and make sure the tongs are secured under both rims of the drum.
3. Carefully move the drum to desired location. When the drum has been completely lowered to the floor or pallet, allow the tongs to slacken and move them away from the drum.

## **SPECIFICATION**

Capacity.....500Kgs / 1100 lbs.  
Drum Size.....55 gallon (210 litre)  
Net Weight.....5Kgs / 7 lbs.